# PORTABLE ELECTRIC FOX

The FOX is a single-phase, portable electric motor from ENAR which is protected by its sturdy, ergonomic housing. It has been designed to transmit power through a transmission which turns, causing an eccentric inside the poker head to spin at 12 000 rpm and generate vibration.

#### Designed & manufactured to a high standard of quality.

Manufactured using high quality materials ensures high resistance & protection (IP44). The FOX uses an oversized motor and double insulation to guarantee its performance in every job condition.





# + Robust & resistant

Against damage.

The matirial used in the housing of the FOX is resistant against impact, and also stable when the product reaches high temperatures from continuos use on heavy workloads.



### + Carbon brushes

With quick release system.

The complete range of portable electric ENAR vibrators use quick release carbon brushes. Making them easy to change. No need to take the product apart.



#### + Encased motor

made for maximum protection.

The FOX is the only concrete vibrator with an independant motor, mounted seperately from the housing, using a small bespoke frame, providing additional protection and facilitates easy product maintenance with fewer spare parts.



# + Manageable

Thanks to its two handles.

The FOX has one handle on top which incorporates a switch and is used to easily hold the motor while in use. Alternatively, the FOX also has a smaller handle at the back which is more comfortable for those using smaller transmissions.

# **TECHNICAL DATA**

MODEL	WEIGHT (Ib)	VOLTAGE (V)	FREQUENCY (Hz)	POWER (W)	DIMENSIONS (LxWxH)(in)	
FOX 115V 2 25 HP	12.8	115-1~	50-60	1 800 W	342x150x216	

- ▶ Highly resistant housing (IP44).
- Diversized motor & double insulation.
- ▶ Other couplings available.
- Includes shoulder strap.

#### **FOX HEADS**

DIAMETER (in)	LENGTH (in)	WEIGHT (Ib)	SPEED (r.p.m)	PERFORMANCE ft³/h
1	11.25	1.7	14 000	33
1.25	14.4	3.7	13 750	46
1.5	13.2	4.2	13 500	56
1.75	13.2	7	12 500	92
2.25	13.5	10	12 000	115

- oversized eccentric.
- ▶ 4 lubricated bearings with double lock.
- ▶ Easily interchanged



## **FLEXIBLE TRANSMISSIONS**

LENGTH (ft)	WEIGHT (Ib)
2	5.75
3.3	6.6
5	7.75
6.6	8.8
9.8	11
13.1	13.25
16.4	15.5
19.7	13.6

- > Reinforced transmissions.
- Vulcanized transmission at the poker end, providing protection to the part of the transmission most likely to wear out or break.



