

A. P. POKERS

NO	DESCRIPTION	QTY	PART NUMBER				
			94194	94179	94178	94192	94193
01	HEAD CAP	1	300101	320101	340101	360101	380101
02	ROLLING BODY	1	300102	320102	340102	360102	380102
03	CASE	1	300103	320103	340103	360103	308103
04	BEARING HOLDER	1	300104	320104	340104	360104	380104
05	COUNTER SPRING	1	300110	320110	340110	340110	360110
06	SPRING HOLDER	1	300105	320105	340105	360105	380105
07	HOSE JOINT	1	300301	340301	340301	360301	360301
08	TRANS SHAFT	1	300106	340106	340106	360106	360106
09	SHAFT JOINT	1	300201	340201	340201	340201	340201
10	HOSE PROTECTOR	1	340302	340302	340302	340302	340302
11	STOP RING	1	340303	340303	340303	340303	340303
12	OIL SEAL	1	530108	530101	530101	530109	530109
13	BEARING	2	550508	550506	550506	550507	550507
14	BEARING	1	550201	550205	550206	550207	550208
15	OIL SEAL	1	530401	530402	530403	530404	530405
16	FLEXIBLE HOSE	1	830134	830134	830134	830134	830134
17	FLEXIBLE SHAFT	1	810134	810134	810134	810134	810134
18	HOSE COUPLING	1	340304	340304	340304	340304	340304
19	SHAFT PLUG	1	340202	340202	340202	340202	340202
20	HEXAGONAL PLUG	1	340203	340203	340203	340203	340203
21	HOSE ADAPTOR	1	340305	340305	340305	340305	340305
22	HEXAGONAL ADAPTOR	1	046310	046310	046310	046310	046310
23	COUPLING HEAD	1	046320	046320	046320	046320	046320
24	BEARING	2	550510	550510	550510	550510	550510
25	CIRCLIP	1	670110	670110	670110	670110	670110
26	CLUTCH	1	046350	046350	046350	046350	046350

MODEL	94194	94179	94178	94192	94193
HEAD DIA mm	32	38	45	50	60
HEAD LENGTH mm	470	492	501	508	503
VIBRATION FREQ (Hz)	210	205	200	200	200
VIBRATION AMP (mm)	1.5	1.7	2.0	2.2	2.4
LENGTH OF FLEX (M)	5 - 10	5 - 10	5 - 10	5 - 10	5 - 10
WEIGHT FOR 6M (Kg)	17 (18.50)	18 (19.50)	19 (20.50)	20 (21.50)	21 (22.50)
DRIVING MOTOR	Suggested power should be above 1.5 hp revolution speed should be 3000 rpm				
DRIVING ENGINE	Suggested power should be 3 hp, while revolution speed should be 3000 rpm				